

## StreamXpress Remote Control API

- ❑ Remote Control of StreamXpress
- ❑ SOAP based
- ❑ C++ Library and WSDL file

### Features

- Remote control of *StreamXpress* functions on same PC or from other PC on the network
- Client and *StreamXpress* communicate using industry-standard SOAP messages
- WSDL file enables automatic generation of SOAP proxy
- Remote-Control (RC) license required on DekTec device that runs *StreamXpress*

Copyright © 2011-2015 by DekTec Digital Video B.V.

DekTec Digital Video B.V. reserves the right to change products or specifications without notice. Information furnished in this document is believed to be accurate and reliable, but DekTec Digital Video assumes no responsibility for any errors that may appear in this material.

## Table of Contents

|  |    |   |    |
|--|----|---|----|
| <b>Features</b> .....                                  | 1  | Struct SpRcRfPars.....                        | 39 |
| <b>Table of Contents</b> .....                         | 2  | Struct SpRcSpiPars.....                       | 40 |
| <b>SpRcApi – Revision History</b> .....                | 3  | Struct SpRcTsoipPars.....                     | 41 |
| <b>1. Using SpRcApi</b> .....                          | 4  | SpRcClient::ClearErrors.....                  | 45 |
| 1.1. Introduction.....                                 | 4  | SpRcClient::GetAsiPars.....                   | 46 |
| 1.2. Running StreamXpress.....                         | 4  | SpRcClient::GetChannelModellingPars.....      | 47 |
| 1.3. Client-Server Communication.....                  | 4  | SpRcClient::GetCmmbPars.....                  | 48 |
| 1.4. Using SpRcApi.....                                | 4  | SpRcClient::GetDvbT2Group.....                | 49 |
| <b>2. Creating a Proxy from WSDL</b> .....             | 5  | SpRcClient::GetDvbT2Pars.....                 | 50 |
| 2.1. SpRc.wsdl.....                                    | 5  | SpRcClient::GetHwNoisePars.....               | 51 |
| 2.2. Generating the Proxy.....                         | 5  | SpRcClient::GetIsdbtPars.....                 | 52 |
| <b>3. Using the Static Link Library</b> .....          | 6  | SpRcClient::GetLqGain.....                    | 53 |
| 3.1. Including and Linking SpRcApi.....                | 6  | SpRcClient::GetModPars.....                   | 54 |
| 3.2. Checking return codes.....                        | 6  | SpRcClient::GetPayoutInfo.....                | 55 |
| 3.3. Connecting to StreamXpress.....                   | 6  | SpRcClient::GetPayoutStatus.....              | 56 |
| 3.4. Playing a file.....                               | 6  | SpRcClient::GetRfPars.....                    | 57 |
| <b>SpRcClient – Session Interface</b> .....            | 8  | SpRcClient::GetSignalSource.....              | 58 |
| SpRcClient::CloseSession.....                          | 8  | SpRcClient::GetSpiPars.....                   | 59 |
| SpRcClient::CreateSpRcClient.....                      | 9  | SpRcClient::GetTsgPars.....                   | 60 |
| SpRcClient::GetRemoteVersion.....                      | 10 | SpRcClient::GetTsoipPars.....                 | 61 |
| SpRcClient::GetRemoteDtapiVersion.....                 | 11 | SpRcClient::GetUseNit.....                    | 62 |
| SpRcClient::GetVersion.....                            | 12 | SpRcClient::Normalise.....                    | 63 |
| SpRcClient::OpenSession.....                           | 13 | SpRcClient::OpenChannelModellingFile.....     | 64 |
| <b>SpRcClient – Application Common Interface</b> ..... | 14 | SpRcClient::OpenFile.....                     | 65 |
| SpRcClient::GetAppInfo.....                            | 14 | SpRcClient::SaveChannelModellingSettings..... | 66 |
| SpRcClient::ShowWindow.....                            | 15 | SpRcClient::SaveSettings.....                 | 67 |
| <b>SpRcClient – Port Selection Interface</b> .....     | 16 | SpRcClient::SetAsiPars.....                   | 68 |
| Struct PortDesc.....                                   | 16 | SpRcClient::SetChannelModellingPars.....      | 69 |
| SpRcClient::ScanPorts.....                             | 19 | SpRcClient::SetCmmbPars.....                  | 70 |
| SpRcClient::SelectPort.....                            | 20 | SpRcClient::SetDvbT2Group.....                | 71 |
| SpRcClient::SelectDtaPlus.....                         | 21 | SpRcClient::SetDvbT2Pars.....                 | 72 |
| <b>SpRcClient – Payout Interface</b> .....             | 22 | SpRcClient::SetHwNoisePars.....               | 73 |
| Struct SpRcAsiPars.....                                | 22 | SpRcClient::SetIsdbtPars.....                 | 74 |
| Struct SpRcCmmbPars.....                               | 24 | SpRcClient::SetLqGain.....                    | 75 |
| Struct SpRcCmPars.....                                 | 25 | SpRcClient::SetLoopFlags.....                 | 76 |
| Struct SpRcCmPaths.....                                | 26 | SpRcClient::SetModPars.....                   | 77 |
| Struct SpRcDvbT2Group.....                             | 27 | SpRcClient::SetPayoutState.....               | 78 |
| Struct SpRcDvbT2Pars.....                              | 28 | SpRcClient::SetRfPars.....                    | 79 |
| Struct SpRcHwNoisePars.....                            | 30 | SpRcClient::SetSignalSource.....              | 80 |
| Struct SpRclsdbtLayerPars.....                         | 31 | SpRcClient::SetSpiPars.....                   | 81 |
| Struct SpRclsdbtPars.....                              | 33 | SpRcClient::SetTsgPars.....                   | 82 |
| Struct SpRcModPars.....                                | 35 | SpRcClient::SetTsoipPars.....                 | 83 |
| Struct SpRcPayoutInfo.....                             | 36 | SpRcClient::SetTsRate.....                    | 84 |
| Struct SpRcPayoutStatus.....                           | 38 | SpRcClient::SetUseNit.....                    | 85 |
|  |    | SpRcClient::WaitForCondition.....             | 86 |

## SpRcApi – Revision History

| Version   | Date       | Change Description  |
|-----------|------------|---|
| V1.6.0.13 | 2015.01.08 | <ul style="list-style-type: none"> <li>• Add GetTsgPars()/SetTsgPars() to control test-generator options</li> </ul>   |
| V1.5.0.12 | 2014.06.25 | <ul style="list-style-type: none"> <li>• Extend SpRcTsoipPars to support double buffering on DTA-2162</li> <li>• Add GetIqGain()/SetIqGain() functions to allow changing IQ gain when playing out IQ signals</li> <li>• Add GetRemoteDtapiVersion() to check the DTAPI version used to build StreamXpress</li> </ul>  |
| V1.4.3.10 | 2014.04.24 | <ul style="list-style-type: none"> <li>• Add support for DVB-S2X and S2L3</li> </ul>  |
| V1.4.2.9  | 2014.02.13 | <ul style="list-style-type: none"> <li>• Bugfix release to fix linking problems</li> </ul>  |
| V1.4.1.8  | 2013.03.01 | <ul style="list-style-type: none"> <li>• Add support for DtaPlus device</li> <li>• Add SetRemux() function to control remultiplexing on modulator ports</li> </ul>  |
| V1.3.0.6  | 2012.05.15 | <ul style="list-style-type: none"> <li>• Add Normalise function</li> <li>• Add Open and SaveChannelModellingSettings function</li> <li>• Add Set and GetSignalSource functions</li> <li>• Add Set and GetUseNit functions</li> <li>• Add variables to RfPars struct: Speclnv, CW, RfEnabledOnStop</li> <li>• Add SaveSettings function</li> </ul>                                   |
| V1.2.0.5  | 2011.09.27 | <ul style="list-style-type: none"> <li>• Add Set and GetCmmbPars functions</li> <li>• Add Set and GetDvbT2Group functions</li> <li>• Add Set and GetHwNoisePars functions</li> <li>• WSDL namespaces, removed "http://localhost:80/SpRc.wsdl"</li> <li>• Add SpRcApiNET .NET WSDL proxy wrapper example code</li> <li>• Synchronized documentation with SpRc source code</li> </ul> |
| V1.1.0.4  | 2010.12.08 | <ul style="list-style-type: none"> <li>• Add Set and GetChannelModellingPars functions</li> <li>• Release of WS-I Basic Profile 1.0a compliant WSDL description; used for automatic proxy generation (for example to be used by Tools like Visual Studio.NET and LabView)</li> <li>• Add ShowWindow function for hiding/showing StreamXpress Window</li> </ul>                      |
| V1.0.0.1  | 2009.02.16 | <ul style="list-style-type: none"> <li>• First release to the field</li> </ul>  |

## 1. Using SpRcApi

### 1.1. Introduction

The StreamXpress Remote-Control API (**SpRcApi**) enables a client application to remotely control the *StreamXpress*, in order to automate the play out of streams. The client can be running on the same PC as the *StreamXpress* or on another PC in the network. Most functions available in the *StreamXpress* GUI are also available through the **SpRcApi**.

In this document, the remotely controlled *StreamXpress* will be interchangeably referred to as "server", "playout server" or "*StreamXpress*".

The client is the application that wishes to remotely control the *StreamXpress*.

### 1.2. Running StreamXpress

To run the *StreamXpress* as playout server it is required that:

1. The DekTec device used for playout with *StreamXpress* contains a remote control (RC) license;
2. The *StreamXpress* is started with the `-rc` option, followed by the TCP port number that is used to connect, e.g. `-rc 9000`.

### 1.3. Client-Server Communication

Client and server communicate with each other using SOAP calls over an IP network, or using the local host. SOAP is a standardized protocol that uses messages formatted in XML to execute remote procedure calls.

Currently, SpRcApi supports version 1.1 of the SOAP protocol.

### 1.4. Using SpRcApi

Basically there are 4 ways to deploy SpRcApi:

- Use the WSDL file in applications that can import WSDL files, e.g. Labview.
- Use the WSDL file to automatically generate client code, commonly called a "proxy". The proxy allows you to call the API methods. Section 2 describes an

example to create a proxy with Visual Studio 2008

- Use the SpRcApiNET example code that includes a .NET "wrapper" for the WSDL generated proxy code.
- For clients written in C++, a library is available that makes the remote-control methods available as C++ methods. This is explained further in Section 3.

The main part of this document describes the classes and API calls in SpRcApi, in C++ syntax. The C++ descriptions are easy to map the equivalent SOAP calls because the WSDL API is structured in a similar way. There is one exception: the SpRcClient constants cannot be used directly, the equivalent integer numbers shall be used.

## 2. Creating a Proxy from WSDL

### 2.1. SpRc.wsdl


The WSDL is contained in the file SpRc.wsdl, which is available in SpRcApi.zip.

The SpRc.wsdl description is a WS-I Basic Profile 1.0a compliant web-service description. This file can be used in several tools to automatically generate client proxy code. For example, LabView and Visual Studio 2008/2010 have the possibility to import the WSDL file.

### 2.2. Generating the Proxy

The steps below describe how to generate proxy code and how to use this code in a C# program in a Visual Studio environment:

1. After creating a C# project, right mouse click on the 'References' and choose option 'Add Service Reference...'
2. In the 'Add Service Reference' dialog select the SpRc.wsdl location, change the Namespace and click on the 'OK' button. This will start the proxy code generation.



Some tools don't accept a file location, for these tools you can use the following address to locate SpRc.wsdl: <http://www.dektec.com/Products/Apps/DT-C-300/SpRc.wsdl>

3. Adapt the generated 'app.config' file to the correct remote IP address and used port number.

```
<client>
  <endpoint
    address = "http://localhost:9000"
    binding = "basicHttpBinding"
    bindingConfiguration = "SpRc"
    contract = "SpRc.SpRcPortType"
    name = "SpRc" />
</client>
```

4. The following C# code shows how to instantiate the generated remote-control client proxy and how to do a few remote-control calls.

The Interface calls and structs are similar to the described SpRcClient API but some differences exist:

- a. The result code can be returned via an out parameter and a parameter can be returned via the return value.
- b. SpRcClient constants cannot be used; the equivalent integer numbers shall be used.

```
// Instantiate .NET generated RC client
SpRc.SpRcPortTypeClient c1 =
    new SpRc.SpRcPortTypeClient();

// Open a session
uint res = c1.OpenSession();

// Scan Ports
SpRc.PortDesc[] ports =
    c1.ScanPorts(out res);

// Select DVB-C Modulation
// ( 9 : SPRC_MOD_J83A )
res = c1.SelectPort(ports[0].Serial,
    ports[0].Port, 9, out status);
```

## 3. Using the Static Link Library

### 3.1. Including and Linking SpRcApi

Four **SpRcApi** configurations are available for static linking: **SpRcApi.lib**, **SpRcApi.d.lib**, **SpRcApiMD.lib** and **SpRcApiMD.d.lib**.

The files with a lowercase 'd' at the end are the debug versions of the DTAPI library.

**SpRcApi(d).lib** has been compiled with the C/C++ Code-Generation Options in VC++ set to: "Use run-time library: Multithreaded." On the compiler command line this corresponds to the **/MT** option.

**SpRcApiMD(d).lib** has been compiled with the C/C++ Code-Generation Options in VC++ set to: "Use run-time library: Multithreaded DLL." On the compiler command line this corresponds to the **/MD** option.

The correct version of the **SpRcApi** library file will automatically be linked, because of a **pragma** directive in **SpRcApi.h**.

Automatic linking can be disabled by defining **\_SPRCAPI\_DISABLE\_AUTO\_LINK** (using **#define** or in the Pre-processor Definitions).

So, to use static link library of the **SpRcApi** follow these steps:

1. Copy **SpRcApi.h**, **DTAPI.h** and either **SpRcApi(d).lib** or **SpRcApiMD(d).lib** to your project or to a standard location visible to VC++.
2. Add **#include "SpRcApi.h"** to each file using **SpRcApi** functions.
3. Compile your application using the Multithreaded DLL (compiler switch **/MD**) or static (compiler switch **/MT**) version of the C run-time library.

#### Notes

- The static library files are available for VC10. Be sure to use this Visual Studio C++ version.
- Using the release version of the static link library with a debug build of your main application may crash your application. This is caused by STL which uses different

lengths of data structures for debug and release builds.

### 3.2. Checking return codes

While using **SpRcApi**, it's important to check the return value after each call of an **SpRcApi** function. The connection to the StreamXpress playout server may get interrupted at any time, so each method call may fail. The exception to the rule is **GetVersion** which cannot fail.

For code clarity, the examples below do not check the return values of method calls. In production-quality code, however, it's essential to add such checks.

### 3.3. Connecting to StreamXpress

The following code establishes a connection to the StreamXpress.

```
// Create remote-control client
SpRcClient* SpRc;
SpRc = SpRcClient::CreateSpRcClient();

// Open a session
unsigned char Ip[] = {127,0,0,1};
SpRc->OpenSession(Ip, 9000);
```

Figure 1. Connecting to the StreamXpress.

The first step is to create an **SpRcClient** object, which represents the connection to the playout server.

The next step is to open a session with the playout server, using **OpenSession**. In this case, using local loopback address 127.0.0.1, a connection is established with the **StreamXpress** running on the same PC as the client application. Other PCs on the network can be reached by specifying their IP address.

### 3.4. Playing a file

The other methods in **SpRcApi** can be used to set parameters and play out a file. To a large extent they speak for themselves.

The code below disables looping, opens a file, starts playout and waits until playout is completed.

```
SpRc->SetLoopFlags(0);  
SpRc->OpenFile(L"C:\\Stream.ts");  
SpRc->SetPlayoutState(SPRC_STATE_PLAY);  
SpRc->WaitForCondition(  
    SPRC_COND_STOPPED, -1);
```

The file is opened in the context of the playout server, which means that C: is the C-disk on the playout server, not on the client.

The following code block plays a file for 10 seconds.

```
SpRc->SetPlayoutState(SPRC_STATE_PLAY);  
Sleep(10000);  
SpRc->SetPlayoutState(SPRC_STATE_STOP);
```

**SpRcClient – Session Interface****SpRcClient::CloseSession**

Close the session with the playout server.

```
SPRC_RESULT CloseSession();
```

**Parameters****Result**

| SPRC_RESULT          | Meaning  |
|----------------------|--|
| SPRC_E_COMMUNICATION | An error has occurred in the communication with the playout server |
| SPRC_OK              | The session with the playout server has been closed successfully   |

**Remarks**

## SpRcClient::CreateSpRcClient

Create client object for issuing remote-control commands to a playout server.

```
static SpRcClient* CreateSpRcClient();
```

### Parameters

### Result

| SPRC_RESULT | Meaning                                       |
|-------------|---|
| NULL        | Remote-control object cannot be created       |
| pointer     | Pointer to StreamXpress remote-control client |

### Remarks

The SpRcApi is initialised with code similar to the following:

```
SpRcClient* SpRcApi = SpRcClient::CreateSpRcClient();  
SPRC_RESULT Result = SpRcApi->OpenSession(IpAddr, PortNr);
```

After creating the client object and opening the session, all remote control commands are issued through the remote-control object **SpRcApi**.

## SpRcClient::GetRemoteVersion

Get **SpRcApi** version number as used in the playout server.

```
virtual void SpRcClient::GetRemoteVersion(  
[out] int& Major           // Major version number  
[out] int& Minor           // Minor version number  
[out] int& BugFix          // Bug fix number  
[out] int& Build           // Build number  
);
```

### Parameters

*Major, Minor, BugFix, Build*

Version number of the **SpRcApi** library which was used in the StreamXpress. For an explanation of **SpRcApi** version numbering, see **SpRcClient::GetVersion**.

### Result

| SPRC_RESULT          | Meaning  |
|----------------------|--|
| SPRC_E_COMMUNICATION | An error has occurred in the communication with the playout server |
| SPRC_OK              | The remote version number has been read successfully               |

### Remarks

## SpRcClient::GetRemoteDtapiVersion

Get DTAPI version number used to build StreamXpress.

```
virtual void SpRcClient::GetRemoteDtapiVersion(  
    [out] int& Major           // Major version number  
    [out] int& Minor          // Minor version number  
    [out] int& BugFix         // Bug fix number  
    [out] int& Build          // Build number  
);
```

### Parameters

*Major, Minor, BugFix, Build*

Version number of the DTAPI library which was used in the StreamXpress build.

### Result

| SPRC_RESULT          | Meaning  |
|----------------------|--|
| SPRC_E_COMMUNICATION | An error has occurred in the communication with the playout server |
| SPRC_OK              | The remote Dtapi version number has been read successfully         |

### Remarks

## SpRcClient::GetVersion

Get version number of the **SpRcApi** client library.

```
virtual void SpRcClient::GetVersion(  
    [out] int& Major           // Major version number  
    [out] int& Minor          // Minor version number  
    [out] int& BugFix         // Bug fix number  
    [out] int& Build          // Build number  
);
```

### Parameters

#### *Major*

Major version number. This number is incremented when a non-backward compatible change is introduced in the StreamXpress remote-control API.

#### *Minor*

Minor version number. This number is incremented when a method is added to the StreamXpress remote-control API in a backward compatible way. For example, a client with version number 1.3.x.x will be able to interoperate with StreamXpress with API version 1.4.x.x.

#### *BugFix*

This number is incremented when a bug in the **SpRcApi** library has been fixed, without functional enhancements.

#### *Build*

The build number is a redundant version number that is incremented with every new version of the **SpRcApi** library.

### Result

| SPRC_RESULT | Meaning         |
|-------------|-----------------|
|             | No return value |

### Remarks

## SpRcClient::OpenSession

Establish a session with the playout server.

```
SPRC_RESULT SpRcClient::OpenSession(  
    [in] unsigned char  IpAddr[4],    // IP address  
    [in] unsigned short PortNr       // Port number  
);
```

### Parameters

*IpAddr*

IP address of the playout server. If the StreamXpress is running on the same machine, 127.0.0.1

*PortNr*

Port number to access the playout server. The port number should match the port specified in the `-rc port` option when starting the StreamXpress.

### Result

| SPRC_RESULT           | Meaning  |
|-----------------------|--|
| SPRC_E_NO_LICK        | The port is not properly licensed for playout and remote control   |
| SPRC_OK               | The session with the playout server has been opened successfully   |
| SPRC_VERSION_CONFLICT | A session with the playout server has been opened, but a version conflict has been detected between the version of the client <b>SpRcApi</b> and that of the server <b>SpRcApi</b> |

### Remarks

The `SpRcClient` object supports a single session. If multiple sessions are required, multiple `SpRcClient` objects must be created.

## SpRcClient – Application Common Interface

### SpRcClient::GetAppInfo

Get information about the application.

```
virtual SPRC_RESULT SpRcClient::GetAppInfo(
    [out] std::wstring&  AppName,      // Application name
    [out] Int&  MajorVersion,        // Major version number
    [out] Int&  MinorVersion,       // Minor version number
    [out] Int&  BugFixVersion,      // Bug-fix version number
    [out] Int&  BuildNumber);      // Build number
);
```

#### Parameters

##### *AppName*

Application name as Unicode string. For the moment, the only application supporting SpRcApi is StreamXpress.

##### *MajorVersion*

Major version number. This number is incremented when the application implements major new functions.

##### *MinorVersion*

Minor version number. This number is incremented when the application implements small updates in functionality, possibly together with bug fixes.

##### *BugFixVersion*

Bug-fix version number. This number is incremented when the only changes relative to the last version of the application are bug fixes.

##### *BuildNumber*

Build number. This number is incremented with new builds of the application. It's never reset to zero so that each version of the application has a different build number.

#### Result

| SPRC_RESULT          | Meaning  |
|----------------------|--|
| SPRC_E_COMMUNICATION | An error has occurred in the communication with the playout server |
| SPRC_OK              | Application information is returned successfully                   |

#### Remarks

## SpRcClient::ShowWindow

Show or hide the *StreamXpress* application window.

```
virtual SPRC_RESULT SpRcClient::ShowWindow(  
    [in] bool Show           // Show or Hide  
);
```

### Parameters

*Show*

Show or hide the *StreamXpress* application window.

### Result

| SPRC_RESULT          | Meaning  |
|----------------------|--|
| SPRC_E_COMMUNICATION | An error has occurred in the communication with the playout server |
| SPRC_OK              | The show or hide operation has been executed successfully          |

### Remarks

## SpRcClient – Port Selection Interface

### Struct PortDesc

Structure describing a physical playout port.

```
struct PortDesc {
    __int64 m_Serial;           // Unique serial number of the device
    int m_TypeNumber;         // Device type number
    int m_Ip[4];              // IP address (for IP ports only)
    int m_Mac [6];           // MAC address (for IP ports only)
    int m_FirmwareVersion;    // Firmware version
    int m_FirmwareVariant;    // Firmware variant
    int m_Port;               // Physical port number
    int m_OutputType;         // Output type (OR-able flags)
    int m_Capabilities;       // Capability flags (OR-able flags)
    int m_InUse;              // Output port already in use?
};

typedef std::vector<SpRcPortDesc> SpRcPortDescs;
typedef SpRcPortDescs::iterator SpRcPortDescIt;
```

### Members

*m\_Serial*

The serial number that uniquely identifies the DekTec device that hosts the playout port.

*m\_TypeNumber*

This integer corresponds to the number in the device's type number, e.g. 245 for the DTU-245.

*m\_Ip*

If the playout port is an IP-network port, this member identifies the IP address. Otherwise, the value of this member is undefined.

*m\_Mac*

If the playout port is an IP-network port, this member identifies the MAC address. Otherwise, the value of this member is undefined.

*m\_FirmwareVersion*

Version number of the firmware loaded on the device that hosts the playout port.

*m\_FirmwareVariant*

Variant of the firmware loaded on the device that hosts the playout port. Some DekTec devices may support multiple variants of the firmware each with different functionality.

*m\_Port*

This integer identifies the physical port number associated with this function. Please refer to DekTec's DTAPI documentation for an overview of physical port numbers per device.

*m\_OutputType*

This field describes the type of stream that can be generated on this playout port. Output types are encoded in flags that may be OR-ed together to indicate that the port supports multiple types.

| Value              | Meaning                                    |
|--------------------|--|
| SPRC_OTYPE_ASI     | DVB-ASI                                    |
| SPRC_OTYPE_ATSC    | ATSC (VSB) modulation                      |
| SPRC_OTYPE_CMMA    | CMMA modulation                            |
| SPRC_OTYPE_DTMB    | DTMB modulation                            |
| SPRC_OTYPE_DVBS    | DVB-S modulation                           |
| SPRC_OTYPE_DVBS2   | DVB-S.2 modulation                         |
| SPRC_OTYPE_DVBT    | DVB-T modulation, includes DVB-H           |
| SPRC_OTYPE_DVBT2   | DVB-T2 modulation                          |
| SPRC_OTYPE_DVBT2MI | DVB-T2MI                                   |
| SPRC_OTYPE_IQ      | IQ samples                                 |
| SPRC_OTYPE_ISDBS   | ISDB-S modulation                          |
| SPRC_OTYPE_ISDBT   | ISDB-T modulation                          |
| SPRC_OTYPE_QAM_A   | QAM modulation, ITU-T J.83 Annex A (DVB-C) |
| SPRC_OTYPE_QAM_B   | QAM modulation, ITU-T J.83 Annex B (US)    |
| SPRC_OTYPE_QAM_C   | QAM modulation, ITU-T J.83 Annex C (Japan) |
| SPRC_OTYPE_SDSI    | Standard-definition SDI                    |
| SPRC_OTYPE_SPI     | DVB-SPI                                    |
| SPRC_OTYPE_TSOIP   | TS-over-IP                                 |

### *m\_Capabilities*

This field describes further capabilities of the playout port. Capabilities are encoded in flags that may be OR-ed together to indicate that the port supports multiple capabilities.

| Value       | Meaning  |
|-------------|--|
| SPRC_ADJLVL | Modulator port has an adjustable output level          |
| SPRC_CM     | Modulator port supports channel modelling              |
| SPRC_DIGIQ  | Modulator port has a digital IQ output                 |
| SPRC_IF     | Modulator port has an IF output                        |
| SPRC_LBAND  | Modulator port can upconvert to L-Band 950 .. 2150MHz  |
| SPRC_UHF    | Modulator port can upconvert to UHF Band 400 .. 862MHz |
| SPRC_VHF    | Modulator port can upconvert to VHF Band 47 .. 470MHz  |

### *m\_InUse*

This status flag indicates whether the playout port is currently being used.

The "in-use" status is a snapshot of the current situation. Attaching to a playout port that is unused may fail because of race conditions with other applications.

| Value            | Meaning  |
|------------------|--|
| SPRC_PORT_CURR   | Port is the currently selected playout port in this remote-control session |
| SPRC_PORT_UNUSED | Port is not used   |
| SPRC_PORT_USED   | Port is used by another application  |

## SpRcClient::ScanPorts

Get information about the ports available for play out.

```
virtual SPRC_RESULT SpRcClient::ScanPorts (  
    [out] SpRcPortDesc& PortDescs    // List of playout ports  
);
```

### Parameters

*PortDescs*

List of playout ports. Refer to **Struct PortDesc** for a description of attributes per port.

### Result

| SPRC_RESULT          | Meaning  |
|----------------------|--|
| SPRC_E_COMMUNICATION | An error has occurred in the communication with the playout server |
| SPRC_OK              | Application information is returned successfully                   |

### Remarks

## SpRcClient::SelectPort

Select a physical port for play out.

```
virtual SPRC_RESULT SpRcClient::SelectPort(
    [in] __int64 Serial,        // Serial number of device to be selected
    [in] int Port;            // Physical port number to be selected
    [in] int Modulation;      // Initial modulation standard
);
```

### Parameters

*Serial*

The serial number that identifies the DekTec device to be selected.

*Port*

Physical port number of port to be selected.

*Modulation*

For modulators only: Initial modulation standard. Use one of the `SPRC_MOD_XXX` constants. Set to 0 otherwise.

### Result

| SPRC_RESULT          | Meaning   |
|----------------------|---|
| SPRC_E_COMMUNICATION | An error has occurred in the communication with the playout server  |
| SPRC_E_MOD_STANDARD  | Initial modulation standard <i>Modulation</i> is not supported on the modulator port                              |
| SPRC_E_NO_LICK       | The port is not properly licensed for playout and remote control  |
| SPRC_E_NOT_FOUND     | Cannot find the playout port identified by <i>Serial</i> and <i>Port</i>  |
| SPRC_E_PORT_USED     | The port could not be selected because it's in use by another instance of the StreamXpress or another application |
| SPRC_OK              | The playout port has been selected successfully   |

### Remarks

The playout server will start without file selected and with parameters set to the defaults for the port.

A list of physical ports available for playout can be obtained with `SpRcClient::ScanPorts`.

## SpRcClient::SelectDtaPlus

Select a DtaPlus device to use as attenuator.

```
virtual SPRC_RESULT SpRcClient::SelectDtaPlus(  
    [in] bool UseDtaPlus,      // Whether a dta-plus should be used or not  
    [in] __int64 Serial,      // Serial number of DtaPlus to be selected  
);
```

### Parameters

*UseDtaPlus*

Set to true to actually start using a Dta-plus.

*Serial*

The serial number that identifies the DekTec device to be selected.

### Result

| SPRC_RESULT          | Meaning   |
|----------------------|---|
| SPRC_E_COMMUNICATION | An error has occurred in the communication with the playout server  |
| SPRC_E_NOT_FOUND     | Cannot find the Dta-plus port identified by <i>Serial</i>   |
| SPRC_E_PORT_USED     | The Dta-plus could not be selected because it's in use by another instance of the StreamXpress or another application |
| SPRC_OK              | The Dta-plus port has been selected successfully  |

### Remarks

## SpRcClient – Payout Interface

### Struct SpRcAsiPars

Payout parameters for a DVB-ASI output port.

```

struct SpRcAsiPars {
    bool   m_Remux;           // Remultiplex yes/no
    int    m_PlayoutRate;    // Only used if Remux is on
    bool   m_BurstMode;     // DVB-ASI burst mode
    int    m_TxMode;        // Transmit mode
    int    m_Polarity;     // Physical polarity of the ASI signal
};

```

### Members

*m\_Remux*

Turn remultiplexing on (true) or off (false). If remultiplexing is on, the StreamXpress adds null packets and adjusts timing information so that the stream is played out at *m\_PlayoutRate*. If remultiplexing is off, the stream is played out at the Transport-Stream rate, and *m\_Playout* is not used.

*m\_PlayoutRate*

DVB-ASI payout rate.

*m\_BurstMode*

Turn DVB-ASI burst mode on (true) or off (false).

*m\_TxMode*

Transmit mode.

| Value              | Meaning  |
|--------------------|--|
| DTAPI_TXMODE_188   | Transport Packets are assumed to be 188 bytes, and are played out as 188-bytes packets.  |
| DTAPI_TXMODE_204   | Transport Packets are assumed to be 204 bytes, and are played out as 204-bytes packets.  |
| DTAPI_TXMODE_ADD16 | Transport Packets are assumed to be 188 bytes, and are played out as 204-bytes packets.  |
| DTAPI_TXMODE_MIN16 | Transport Packets are assumed to be 204 bytes, and are played out as 188-bytes packets.  |
| DTAPI_TXMODE_RAW   | No assumptions are made on packet structure. Bytes in the stream are transmitted unmodified. Null-packet stuffing cannot be applied. |

*m\_Polarity*

Polarity of the DVB-ASI signal.

| Value                       | Meaning                         |
|-----------------------------|---------------------------------|
| <b>DTAPI_TXPOL_NORMAL</b>   | Generate a 'normal' ASI signal  |
| <b>DTAPI_TXPOL_INVERTED</b> | Generate an inverted ASI signal |

## Struct SpRcCmmbPars

CMMB parameters.

```
struct SpRcCmmbPars {  
    int  m_Bandwidth;           // CMMB Bandwidth  
    int  m_AreaId;             // Area ID (0..127)  
    int  m_TxId;               // Transmitter ID (128..255)  
};
```

### Members

*m\_Bandwidth*

CMMB Bandwidth.

| Value              | Meaning             |
|--------------------|---------------------|
| DTAPI_CMMB_BW_2MHZ | CMMB 2MHz Bandwidth |
| DTAPI_CMMB_BW_8MHz | CMMB 8MHz Bandwidth |

*m\_AreaId*

Area ID (0..127).

*m\_TxId*

Transmitter ID (128..255).

## Struct SpRcCmPars

Channel-modelling parameters.

```
struct SpRcCmPars {  
    bool m_CmEnable;           // Enable channel modelling  
    bool m_AwgnEnable;        // Enable noise injection  
    bool m_PathsEnable;       // Enable transmission path simulation  
    double m_Snr;             // Signal-to-noise ratio in dB  
    std::vector<SpRcCmPath> m_Paths; // List of transmission paths  
};
```

### Members

*m\_CmEnable*

If true, perform channel modelling according to the other values in this struct.  
If false, channel modelling is disabled and the other struct values are ignored.

*m\_AwgnEnable*

Enable white noise injection; *m\_Snr* specifies the signal to noise ratio.

*m\_PathsEnable*

Enable multipath echo simulation.

*m\_Snr*

The noise power is defined relative to an imaginative 0dB output signal of the modulator. This means that *m\_Snr* is the real signal-to-noise ratio only if the accumulated power of the paths in *m\_Paths* is 0dB.

*m\_Paths*

List of transmission-path descriptions (maximum 32). See struct **SpRcCmPath**.

## Struct SpRcCmPaths

Channel-modelling parameters for a single .

```

struct SpRcCmPath {
    int   m_Type;           // Type of path fading
    double m_Attenuation;   // Attenuation in dB
    double m_Delay;        // Delay in us
    double m_Phase;        // Phase shift in degrees
    double m_Doppler;      // Doppler Frequency in Hz
};

```

### Members

*m\_Type*

Type of transmission path values:

| Value                         | Meaning   |
|-------------------------------|---|
| <b>SPRC_CONSTANT_DELAY</b>    | Constant delay and phase  |
| <b>SPRC_CONSTANT_DOPPLER</b>  | Constant frequency shift  |
| <b>SPRC_RAYLEIGH_JAKES</b>    | Raleigh fading with Jakes power spectral density (mobile path model)        |
| <b>SPRC_RAYLEIGH_GAUSSIAN</b> | Raleigh fading with Gaussian power spectral density (ionspheric path model) |

*m\_Attenuation*

Attenuation in dB. The total attenuation of all paths may not exceed 0dB to avoid overflow of the channel simulator.

*m\_Delay*

Delay in us. The maximum delay for an 8MHz channel is 896us.

*m\_Phase*

Phase shift in degrees (value ignored for type **RAYLEIGH\_JAKES** and **RAYLEIGH\_GAUSSIAN**).

*m\_Doppler*

Doppler frequency in Hz (value ignored for type **CONSTANT\_DELAY**). The corresponding Speed in m/s is:  $Speed = f_{doppler} * 3.10^8 / f_{RF}$ .

## Struct SpRcDvbT2Group

Parameters to specify standard DVB-T2 parameter set groups

```
struct SpRcDvbT2Group {  
    std::wstring m_GroupName; // Name of the DVB-T2 group  
    std::wstring m_GroupRefName; // Specific set in group  
};
```

### Members

*m\_GroupName*

Name of the DVB-T2 group, e.g. "VV1xx".

*m\_GroupRefName*

Specific set in group, e.g. "VV100".

## Struct SpRcDvbT2Pars

Structure describing DVB-T2 modulation parameters.

```

struct SpRcDvbT2Pars {
    int   m_Bandwidth;           // DVB-T2 channel bandwidth
    int   m_FftMode;            // FFT mode (or size)
    int   m_Miso;               // MISO mode
    int   m_GuardInterval;     // Guard interval
    int   m_Papr;               // PAPR reduction mode
    int   m_BwtExt;            // Bandwidth extension
    int   m_PilotPattern;      // Pilot pattern
    int   m_NumT2Frames;       // Number of T2 frames in a super frame
    int   m_NumDataSyms;      // Number of data OFDM symbols per T2 frame
    int   m_L1Modulation;     // L1 modulation type
    bool  m_FefEnable;        // Insert FEF (yes/no)
    int   m_FefType;          // FEF type
    int   m_FefLength;        // FEF length
    int   m_FefS1;            // FEF S1 field value
    int   m_FefS2;            // FEF S2 field value
    int   m_FefInterval;     // FEF interval
    int   m_FefSignal;        // Type of signal during FEF period
    int   m_CellId;           // Cell ID
    int   m_NetworkId;        // Network ID
    int   m_T2SystemId;       // T2 system ID
    int   m_Frequency;        // L1-post frequency field value
    // PLP#0 parameters
    bool  m_Hem;              // High Efficiency Mode (yes/no)
    bool  m_Npd;              // Null Packet Deletion (yes/no)
    bool  m_IssyEnabled;     // ISSY enabled (yes/no)
    int   m_Id;               // PLP ID
    int   m_GroupId;         // PLP group ID
    int   m_Type;            // PLP type
    int   m_CodeRate;        // Code rate
    int   m_Modulation;      // Modulation type
    bool  m_Rotation;        // Constellation rotation (yes/no)
    int   m_FecType;         // FEC type
    int   m_TimeIlLength;    // Time interleaving length
    int   m_TimeIlType;     // Time interleaving type
    bool  m_InBandFlag;     // In band signalling information (yes/no)
    bool  m_NumBlocks;      // Number of FEC blocks per IL frame
    int   m_FollowMode;     // Mode to compute NumDataSyms/NumBlocks
};

```

### Members

*m\_Bandwidth, m\_FftMode, m\_Miso, m\_GuardInterval, m\_Papr, m\_BwtExt, m\_PilotPattern, m\_NumT2Frames, m\_NumDataSyms, m\_L1Modulation, m\_FefEnable, m\_FefType, m\_FefLength, m\_FefS1, m\_FefS2, m\_FefInterval, m\_FefSignal, m\_CellId, m\_NetworkId, m\_T2SystemId, m\_Frequency*

Overall DVB-T2 modulation parameters that are not specific per PLP. For a description of these parameters, please refer to the section describing **DtDvbT2Pars** in the DTAPI specification.

*m\_Hem, m\_Npd, m\_IssyEnabled, m\_Id, m\_GroupId, m\_Type, m\_CodeRate, m\_Modulation, m\_Rotation, m\_FecType, m\_TimeIlLength, m\_TimeIlType, m\_InBandFlag, m\_NumBlocks*

Parameters for PLP 0 (the one and only PLP). For a description of these parameters, please refer to the section describing **struct DtDvbT2PlpPars** in the DTAPI specification.

*m\_FollowMode*

This parameter specifies how StreamXpress computes or copies **NUM\_DATA\_SYMBOLS** (the number of data OFDM symbols per T2 frame) and **PLP\_NUM\_BLOCKS** (the number of FEC blocks per interleaving frame.)

| Value                      | Meaning   |
|----------------------------|---|
| <b>SPRC_T2_FOLLOW_OFF</b>  | No automatic computations.<br><b>NUM_DATA_SYMBOLS</b> is copied from <i>m_NumDataSyms</i> , while <b>PLP_NUM_BLOCKS</b> is copied from <i>m_NumBlocks</i>   |
| <b>SPRC_T2_FOLLOW_OPT1</b> | Compute <b>NUM_DATA_SYMBOLS</b> and <b>PLP_NUM_BLOCKS</b> .<br>Given the DVB-T2 modulation parameters in <b>SpRcDvbT2Pars</b> , the StreamXpress optimises both <b>NUM_DATA_SYMBOLS</b> and <b>PLP_NUM_BLOCKS</b> . The values in <i>m_NumDataSyms</i> and <i>m_NumBlocks</i> are not used.         |
| <b>SPRC_T2_FOLLOW_OPT2</b> | Compute <b>PLP_NUM_BLOCKS</b> .<br>Given the DVB-T2 modulation parameters in <b>SpRcDvbT2Pars</b> including <i>m_NumDataSyms</i> , the StreamXpress optimises <b>PLP_NUM_BLOCKS</b> . The value in <i>m_NumBlocks</i> is not used.<br><b>NUM_DATA_SYMBOLS</b> is copied from <i>m_NumDataSyms</i> . |

## Struct SpRcHwNoisePars

Noise parameters for modulators DTA-107 and DTA-2107.

```
struct SpRcHwNoisePars {  
    bool   m_SnrOn;           // Enable Noise generator  
    double m_Snr;            // Signal Noise ratio  
};
```

### Members

*m\_SnrOn*  
Enable Noise generator.

*m\_Snr*  
Signal-to-noise ratio in dB.

## Struct SpRcIsdbtLayerPars

Structure describing ISDB-T modulation parameters for one hierarchical layer. This structure is used in `SpRcIsdbtPars`, in an array of three structs for layer A, B and C.

```

struct SpRcIsdbtLayerPars {
    int  m_NumSegments;           // Number of segments
    int  m_Modulation;           // Modulation type
    int  m_CodeRate;             // Code rate
    int  m_TimeInterleave;       // Time interleaving
};

```

### Members

*m\_NumSegments*

Number of segments used in this layer. The sum of *m\_NumSegment* must be 13.

*m\_Modulation*

Modulation type applied to the segments in this layer.

| Value                 | Meaning |
|-----------------------|---------|
| DTAPI_ISDBT_MOD_DQPSK | DQPSK   |
| DTAPI_ISDBT_MOD_QPSK  | QPSK    |
| DTAPI_ISDBT_MOD_QAM16 | 16-QAM  |
| DTAPI_ISDBT_MOD_QAM64 | 64-QAM  |

*m\_CodeRate*

Convolutional coding rate applied to the segments in this layer.

| Value                | Meaning |
|----------------------|---------|
| DTAPI_ISDBT_RATE_1_2 | 1/2     |
| DTAPI_ISDBT_RATE_2_3 | 2/3     |
| DTAPI_ISDBT_RATE_3_4 | 3/4     |
| DTAPI_ISDBT_RATE_5_6 | 5/6     |
| DTAPI_ISDBT_RATE_7_8 | 7/8     |

*m\_TimeInterleave*

Encoded length of time interleaving.

The table below defines the mapping of  $m\_TimeInterleave$  to parameter  $l$  in the time-interleaving process.

| Value | Mode 1 | Mode 2 | Mode 3 |
|-------|--------|--------|--------|
| 0     | 0      | 0      | 0      |
| 1     | 4      | 2      | 1      |
| 2     | 8      | 4      | 2      |
| 3     | 16     | 8      | 4      |

## Struct SpRcIsdbtPars

Modulation parameters for ISDB-T.

```

struct SpRcIsdbtPars {
    bool m_DoMux; // Hierarchical multiplexing yes/no
    int m_BType; // Broadcast type
    int m_Mode; // Transmission mode
    int m_Guard; // Guard interval
    int m_PartialRx; // Partial reception
    int m_Emergency; // Switch-on control for emergency broadcast
    int m_IipPid; // PID used for multiplexing IIP packet
    SpRcIsdbtLayerPars m_LayerPars[3]; // Layer-A/B/C parameters
    std::map<int, int> m_Pid2Layer; // PID-to-layer map
    int m_LayerOther; // Other PIDs are mapped to this layer
    int m_ParXtra0; // Extra parameters
    int m_Virtual13Segm; // Virtual 13-segment mode
};

struct SpRcIsdbtLayerPars {
    int m_NumSegment; // Number of segments
    int m_Modulation; // Modulation type
    int m_CodeRate; // Code rate
    int m_TimeInterleave; // Time interleaving
};

```

### Members

*m\_DoMux*

If true, perform hierarchical multiplexing in accordance with the ISDB-T parameters as defined explicitly in this structure.

If false, the ISDB-T modulation parameters are specified indirectly by the TMCC information in the 16 extra bytes of the 204-byte packets.

*m\_BType*

Broadcast type.

| Value                  | Meaning   |
|------------------------|---|
| DTAPI_ISDBT_BTYPE_TV   | TV broadcast; Can be used with any number of segments |
| DTAPI_ISDBT_BTYPE_RAD1 | 1-segment radio broadcast; Total #segments must be 1  |
| DTAPI_ISDBT_BTYPE_RAD3 | 3-segment radio broadcast; Total #segments must be 3  |

*m\_Mode*

Transmission mode.

| Value | Meaning    |
|-------|------------|
| 1     | Mode 1: 2k |
| 2     | Mode 2: 4k |
| 3     | Mode 3: 8k |

*m\_Guard*

Guard-interval length.

| Value                  | Meaning |
|------------------------|---------|
| DTAPI_ISDBT_GUARD_1_32 | 1/32    |
| DTAPI_ISDBT_GUARD_1_16 | 1/16    |
| DTAPI_ISDBT_GUARD_1_8  | 1/8     |
| DTAPI_ISDBT_GUARD_1_4  | 1/4     |

*m\_PartialRx*

Flag that indicates whether layer A is used for partial reception: 0 = no partial reception, 1 = partial reception on.

*m\_Emergency*

Flag that indicates whether the switch-on control flag for emergency broadcast should be turned on: 0 = off, 1 = on.

*m\_IipPid*

PID value used for multiplexing the IIP packet.

*m\_LayerPars*

Modulation parameters for hierarchical layers A (element 0), B (1) and C (2).

*m\_Pid2Layer*

Map that specifies the hierarchical layer, or layers, to which an elementary stream is to be mapped. The key in the map is the PID of the elementary stream. The value stored in the map is an OR of one or more flags listed in the table below. A value of 0 indicates that the elementary stream is to be dropped.

| Value               | Meaning                          |
|---------------------|----------------------------------|
| DTAPI_ISDBT_LAYER_A | Map elementary stream to layer A |
| DTAPI_ISDBT_LAYER_B | Map elementary stream to layer B |
| DTAPI_ISDBT_LAYER_C | Map elementary stream to layer C |

*m\_LayerOther*

Map streams with PIDs not in *m\_Pid2Layer* to this layer.

*m\_ParXtra0*

Extra parameter encoding bandwidth, sample rate and number of segments. This parameter is encoded like ParXtra0 in SetModControl with *ModType* DTAPI\_MOD\_ISDBT.

*m\_Virtual13Segm*

Use virtual 13 segment mode. The number of segments in layer B is "faked" to be 12.

## Struct SpRcModPars

Modulation parameters for all modulation standards except DVB-T2 and ISDB-T.

```
struct SpRcModPars {  
    int m_ModType;           // Modulation type  
    int m_ParXtra0;         // Extra modulation parameter 0  
    int m_ParXtra1;         // Extra modulation parameter 1  
    int m_ParXtra2;         // Extra modulation parameter 2  
    int m_SymRate;          // Symbol rate in bd  
};
```

### Members

*m\_ModType*

Modulation type, see DTAPI\_MOD\_XXX constants.

*m\_ParXtra0*, *m\_ParXtra1*, *m\_ParXtra2*

Modulation parameters, see DTAPI documentation ([SetModControl](#)).

*m\_SymRate*

Symbol rate in baud. Required for modulation standards that require a symbol rate, like DVB-S. This member should be set to -1 if no symbol rate is required.

## Struct SpRcPlayoutInfo

Structure describing static playout information.

```

struct SpRcPlayoutInfo {
    bool   m_BurstMode;           // DVB-ASI burst mode
    bool   m_ExtClock;           // Use external clock
    bool   m_FileCanBeRead;      // A file has been selected that can be read
    std::wstring m_Filename;     // Currently selected filename
    long   m_FileOffsetEnd;      // Number of unused bytes at end of file
    long   m_FileOffsetStart;    // Number of unused bytes at start of file
    long   m_FilePlayedBytes;    // File length minus bytes at start and end
    int    m_FileRateEst;        // TS: Estimated file rate
    long   m_FileSize;           // Size of the file
    int    m_FileType;           // Type of data in file: RAW/TS/SDI
    double m_LoopBeginRel;       // Subloop, begin position (relative 0..1)
    double m_LoopEndRel;        // Subloop, end position (relative 0..1)
    int    m_LoopFlags;          // Adapt CC/PCR/TDT and wrap-around flags
    int    m_PlayoutState;       // HOLD/PLAYING
    int    m_PlayoutRate;        // Playout rate @188
    boolean m_Remux;            // Remultiplex mode
    int    m_SymRate;            // Modulators: Symbol rate
    double m_TimeLoopBegin;     // Time corresponding to beginning of loop
    double m_TimeLoopEnd;       // Time corresponding to end of loop
    int    m_TimeOffset;        // Offset added to playout time
    int    m_TsRate;             // TS: TS rate @188
    int    m_TpSize;             // TS: packet size
    int    m_TxPolarity;        // Transmit polarity for ASI channels
};

```

### Members

*m\_BurstMode*

For ASI channels: DVB-ASI is sent in burst mode yes/no.

*m\_ExtClock*

The transport-stream is taken from the external-clock input.

*m\_FileCanBeRead*

The file that is currently selected is valid.

*m\_Filename*

The name of the file that is currently selected in *StreamXpress*.

*m\_FileOffsetEnd*

Number of unused bytes at the end of the file.

*m\_FileOffsetStart*

Number of unused bytes at start of the file.

*m\_FilePlayedBytes*

The number of bytes from the file that are actually played out (file length minus number of unused bytes at start and end).

*m\_FileRateEst*

TS: Estimated file rate.

*m\_FileSize*

Size of the file.

*m\_FileType*

Type of data in the file: raw data, transport stream or SDI.

*m\_LoopBeginRel*

Start position of the subloop as a relative number between 0 and 1. If a subloop is not used, the value is 0.

*m\_LoopEndRel*

End position of the subloop as a relative number between 0 and 1. If a subloop is not used, the value is 0.

*m\_LoopFlags*

Loop adaptation flags: Adaptation of CC, PCR, TDT and wrap-around flags.

*m\_PlayoutState*

Indicates whether the StreamXpress is paused (hold mode) or playing.

*m\_PlayoutRate*

Rate at which the stream is played. For transport streams, the rate at 188 bytes per packet is used, even if the stream contains 204-byte transport packets.

*m\_Remux*

For transport streams only: Indicates whether the transport-stream is re-multiplexed to another rate.

*m\_SymRate*

For modulators only: Symbol rate.

*m\_TimeLoopBegin*

Playout time corresponding to the beginning of the loop.

*m\_TimeLoopEnd*

Playout time corresponding to the end of loop.

*m\_TimeOffset*

Offset that is added to the playout time.

*m\_TsRate*

Rate of the transport stream in the. For transport streams, the rate at 188 bytes per packet is used, even if the file contains 204-byte transport packets.

*m\_TpSize*

For transport streams only: size of the transport packets.

*m\_TxPolarity*

Transmit polarity for ASI channels.

## Struct SpRcPlayoutStatus

Structure describing the dynamic playout status.

```
struct SpRcPlayoutInfo {  
    int    m_FifoLoad;           // Current FIFO load  
    int    m_NumErrors;        // Number of errors (underflows)  
    int    m_NumWraps;         // #wraps  
    double m_PosRel;           // Relative position in subloop (0..1)  
    int    m_TotalMemLoad;     // #bytes in DiskBuffer+MemBuffer (snapshot)  
};
```

### Members

*m\_FifoLoad*

Current load of the output FIFO.

*m\_NumErrors*

Number of underflow errors since the last start of playout.

*m\_NumWraps*

Number of times that the file has wrapped since the last start of playout.

*m\_PosRel*

Relative position in the subloop. The client can use *m\_PosRel* to synchronise a slider to the slider in the **StreamXpress**.

*m\_TotalMemLoad*

Snapshot of the number of data bytes stored in the disk and memory buffer.

## Struct SpRcRfPars

Structure describing RF parameters for modulators.

```
struct SpRcRfPars {  
    __int64 m_Frequency;    // RF frequency (Hz)  
    double m_Level;        // RF output level (dBm)  
    bool m_SpecInv;        // RF Spectral inversion  
    bool m_CW;             // RF CW mode  
    bool m_RfEnabledOnStop; // RF output enabled on stop  
};
```

### Members

*m\_Frequency*

Center frequency in Hz of the upconverted signal.

*m\_Level*

Level of the main output signal in dBm.

*m\_SpecInv*

Spectral inversion.

*m\_CW*

CW.

*m\_RfEnabledOnStop*

Whether or not the RF output is muted when playback is stopped.

## Struct SpRcSpiPars

Playout parameters for a DVB-SPI output port.

```

struct SpRcSpiPars {
    bool   m_Remux;           // Remultiplex yes/no
    int    m_PlayoutRate;    // Only used if Remux is on
    int    m_TxMode;         // Transmit mode
    bool   m_Power;         // Turn power on/off for external adapter
};

```

### Members

*m\_Remux*

Turn remultiplexing on (true) or off (false). If remultiplexing is on, the StreamXpress adds null packets and adjusts timing information so that the stream is played out at *m\_PlayoutRate*. If remultiplexing is off, the stream is played out at the Transport-Stream rate, and *m\_Playout* is not used.

*m\_PlayoutRate*

DVB-SPI playout rate.

*m\_TxMode*

Transmit mode.

| Value              | Meaning  |
|--------------------|--|
| DTAPI_TXMODE_188   | Transport Packets are assumed to be 188 bytes, and are played out as 188-bytes packets.  |
| DTAPI_TXMODE_192   | 192-byte mode (DTA-102 only)<br>Transport Packets are assumed to be 192 bytes, and are played out as 192-bytes packets.              |
| DTAPI_TXMODE_204   | Transport Packets are assumed to be 204 bytes, and are played out as 204-bytes packets.  |
| DTAPI_TXMODE_ADD16 | Transport Packets are assumed to be 188 bytes, and are played out as 204-bytes packets.  |
| DTAPI_TXMODE_MIN16 | Transport Packets are assumed to be 204 bytes, and are played out as 188-bytes packets.  |
| DTAPI_TXMODE_RAW   | No assumptions are made on packet structure. Bytes in the stream are transmitted unmodified. Null-packet stuffing cannot be applied. |

*m\_Power*

Power for external adapter is switched on or off.

## Struct SpRcTsgPars

Parameters for the test-signal generator.

```
struct SpRcTsgPars {
    int m_Type;           // Type of signal generator to use
    int m_Pid;           // PID to carry the signal for TS modes
    int m_VidStd;        // Video standard for SDI modes
    int m_Flags;         // Reserved, set to 0
};
```

### Members

*m\_Type*

Type of signal generator to use:

| Value                | Meaning              |
|----------------------|----------------------|
| SPRC_TSG_TYPE_PRBS7  | PRBS-7 TS generator  |
| SPRC_TSG_TYPE_PRBS15 | PRBS-15 TS generator |
| SPRC_TSG_TYPE_PRBS23 | PRBS-23 TS generator |
| SPRC_TSG_TYPE_PRBS31 | PRBS-31 TS generator |
| SPRC_TSG_TYPE_SDI    | SDI generator        |

*m\_Pid*

PID to carry the PRBS packets. Ignored while in SDI mode.

*m\_VidStd*

Video standard used for SDI signal generator. Ignored while in transport-stream mode.

| Value                  | Meaning |
|------------------------|---------|
| SPRC_VIDSTD_525I59_94  |         |
| SPRC_VIDSTD_625I50     |         |
| SPRC_VIDSTD_720P23_98  |         |
| SPRC_VIDSTD_720P24     |         |
| SPRC_VIDSTD_720P25     |         |
| SPRC_VIDSTD_720P29_97  |         |
| SPRC_VIDSTD_720P30     |         |
| SPRC_VIDSTD_720P50     |         |
| SPRC_VIDSTD_720P59_94  |         |
| SPRC_VIDSTD_720P60     |         |
| SPRC_VIDSTD_1080I50    |         |
| SPRC_VIDSTD_1080I59_94 |         |
| SPRC_VIDSTD_1080I60    |         |
| SPRC_VIDSTD_1080P23_98 |         |
| SPRC_VIDSTD_1080P24    |         |
| SPRC_VIDSTD_1080P25    |         |
| SPRC_VIDSTD_1080P29_97 |         |
| SPRC_VIDSTD_1080P30    |         |
| SPRC_VIDSTD_1080P50    |         |
| SPRC_VIDSTD_1080P59_94 |         |
| SPRC_VIDSTD_1080P60    |         |

*m\_Flags*

Reserved, set to 0.

## Struct SpRcTsoipPars

Parameters for a Transport-Stream-over-IP port.

```

struct SpRcTsoipPars {
    int m_TxMode; // Transmission mode (188, 204, Add16, ...)
    unsigned char m_Ip[4]; // IP address
    int m_Port; // Port number
    bool m_EnaFallover; // Enable IP double-buffering
    unsigned char m_Ip2[4]; // 2nd IP address, used for double-buffering
    int m_Port2; // 2nd port number, used for double-buffering
    int m_TimeToLive; // TTL
    int m_NumTpPerIp; // #TPs per IP packet
    int m_Protocol; // Protocol: UDP/RTP
    int m_DiffServ; // Differentiated services
    int m_FecMode; // Error correction mode
    int m_FecNumRows; // 'D' = #rows in FEC matrix
    int m_FecNumCols; // 'L' = #columns in FEC matrix
};

```

### Members

*m\_TxMode*

Transmit mode.

| Value              | Meaning   |
|--------------------|---|
| DTAPI_TXMODE_188   | Transport Packets are assumed to be 188 bytes, and are played out as 188-bytes packets. |
| DTAPI_TXMODE_204   | Transport Packets are assumed to be 204 bytes, and are played out as 204-bytes packets. |
| DTAPI_TXMODE_ADD16 | Transport Packets are assumed to be 188 bytes, and are played out as 204-bytes packets. |
| DTAPI_TXMODE_MIN16 | Transport Packets are assumed to be 204 bytes, and are played out as 188-bytes packets. |

*m\_Ip[4]*

Destination IP address. If the IP address is in the multicast range, the playout server automatically joins and drops membership of the multicast group.

*m\_Port*

Destination port number.

*m\_EnaFallover*

Enable IP double-buffering. Currently only supported on the DTA-2162. The second IP port will playout a duplicate of the signal which can be used by a receiver to conceal errors in either of the two transmission paths.

*m\_Ip2[4]*

*m\_Port2*

See *m\_Ip* and *m\_Port*. Used if *m\_EnaFallover* is true to configure the second IP port.

*m\_TimeToLive*

Time-To-Live (TTL) value to be used for multicast transmission. When *m\_Ttl* is 0, a default value is used.

*m\_NumTpPerIp*

Number of Transport Packets (TPs) stored in one IP packet. The range is 1..7.

*m\_Protocol*

Protocol expected for encapsulation of Transport Packets.

| Value           | Meaning |
|-----------------|---------|
| DTAPI_PROTO_UDP | UDP     |
| DTAPI_PROTO_RTP | RTP     |

*m\_DiffServ*

Value to be put in the *Differentiated Services* field (formerly *Service Type*) in the IP header.

*m\_FecMode*

Error-correction mode.

| Value             | Meaning   |
|-------------------|---|
| DTAPI_FEC_DISABLE | No FEC  |
| DTAPI_FEC_2D      | RFC2733 parity FEC with 2D extensions as described in Code of Practice #3 |

*m\_FecNumRows*, *m\_FecNumCols*

Number of rows and columns in the FEC matrix. In the *COP #3* these parameters are called *D* and *L* respectively. The following restrictions apply to *L* and *D*:

$$4 \leq D \leq 20, \quad 1 \leq L \leq 20 \quad \text{and} \quad L * D \leq 100$$

## SpRcClient::ClearErrors

Clear number-of-errors counter.

```
virtual SPRC_RESULT SpRcClient::ClearErrors(  
);
```

### Parameters

### Result

| SPRC_RESULT          | Meaning  |
|----------------------|--|
| SPRC_E_COMMUNICATION | An error has occurred in the communication with the playout server |
| SPRC_E_NO_PORT       | Invalid operation because no port is selected                      |
| SPRC_OK              | The DVB-ASI transmission parameters have been read successfully    |

### Remarks

## SpRcClient::GetAsiPars

Get DVB-ASI transmission parameters.

```
virtual SPRC_RESULT SpRcClient::GetAsiPars (  
    [out] SpRcAsiPars& AsiPars // ASI parameters  
);
```

### Parameters

*AsiPars*

DVB-ASI transmission parameters, see **Struct SpRcAsiPars**.

### Result

| SPRC_RESULT          | Meaning   |
|----------------------|---|
| SPRC_E_COMMUNICATION | An error has occurred in the communication with the playout server                |
| SPRC_E_NO_PORT       | Invalid operation because no port is selected                                     |
| SPRC_E_NOT_ASI       | Invalid operation because the port is not an ASI port or is operating in SDI mode |
| SPRC_OK              | The DVB-ASI transmission parameters have been read successfully                   |

### Remarks

## SpRcClient::GetChannelModellingPars

Get Channel Modelling parameters.

```
virtual SPRC_RESULT SpRcClient::GetChannelModellingPars(  
    [out] SpRcCmPars& CmPars           // Channel Modelling parameters  
);
```

### Parameters

*CmPars*

Channel Modelling parameters, see **Struct SpRcCmPars**.

### Result

| SPRC_RESULT          | Meaning  |
|----------------------|--|
| SPRC_E_COMMUNICATION | An error has occurred in the communication with the playout server |
| SPRC_E_NO_PORT       | Invalid operation because no port is selected                      |
| SPRC_E_NOT_MOD       | Invalid operation because the port is not a modulation port        |
| SPRC_OK              | The Channel Modelling parameters have been read successfully       |

### Remarks

## SpRcClient::GetCmmbPars

Get CMMB parameters.

```
virtual SPRC_RESULT SpRcClient::GetCmmbPars (  
    [out] SpRcCmmbPars& CmmbPars // CMMB parameters  
);
```

### Parameters

*CmmbPars*

CMMB parameters, see **Struct SpRcCmmbPars**.

### Result

| SPRC_RESULT          | Meaning  |
|----------------------|--|
| SPRC_E_COMMUNICATION | An error has occurred in the communication with the playout server |
| SPRC_E_NO_PORT       | Invalid operation because no port is selected                      |
| SPRC_E_NOT_CMMB      | Invalid operation because the CMMB modulation is not configured    |
| SPRC_E_NOT_MOD       | Invalid operation because the port is not a modulation port        |
| SPRC_OK              | The parameters have been read successfully                         |

### Remarks

## SpRcClient::GetDvbT2Group

Get current DVB-T2 group selection.

```
virtual SPRC_RESULT SpRcClient::GetDvbT2Group(  
    [out] SpRcDvbT2Group& DvbT2Group // DVB-T2 group  
);
```

### Parameters

*DvbT2Group*

DVB-T2 group, see Struct `SpRcDvbT2Group`.

### Result

| SPRC_RESULT          | Meaning  |
|----------------------|--|
| SPRC_E_COMMUNICATION | An error has occurred in the communication with the playout server |
| SPRC_E_NO_PORT       | Invalid operation because no port is selected                      |
| SPRC_E_NOT_DVBT2     | Invalid operation because the DVB-T2 modulation is not configured  |
| SPRC_E_NOT_MOD       | Invalid operation because the port is not a modulation port        |
| SPRC_OK              | The parameters have been read successfully                         |

### Remarks

## SpRcClient::GetDvbT2Pars

Get DVB-T2 parameters.

```
virtual SPRC_RESULT SpRcClient::GetDvbT2Group(
    [out] SpRcDvbT2Pars& DvbT2Pars // DVB-T2 parameters
);
```

### Parameters

*DvbT2Pars*

DVB-T2 parameters, see **Struct SpRcDvbT2Pars**.

### Result

| SPRC_RESULT          | Meaning  |
|----------------------|--|
| SPRC_E_COMMUNICATION | An error has occurred in the communication with the playout server |
| SPRC_E_NO_PORT       | Invalid operation because no port is selected                      |
| SPRC_E_NOT_DVBT2     | Invalid operation because the DVB-T2 modulation is not configured  |
| SPRC_E_NOT_MOD       | Invalid operation because the port is not a modulation port        |
| SPRC_OK              | The parameters have been read successfully                         |

### Remarks

## SpRcClient::GetHwNoisePars

Get Noise parameters for modulators DTA-107 and DTA-2107.

```
virtual SPRC_RESULT SpRcClient::GetHwNoisePars (  
    [out] SpRcHwNoisePars& HwNoisePars // Hw Noise parameters  
);
```

### Parameters

*HwNoisePars*

Noise parameters, see Struct `SpRcHwNoisePars`.

### Result

| SPRC_RESULT          | Meaning  |
|----------------------|--|
| SPRC_E_COMMUNICATION | An error has occurred in the communication with the playout server |
| SPRC_E_NO_PORT       | Invalid operation because no port is selected                      |
| SPRC_E_NOT_MOD       | Invalid operation because the port is not a modulation port        |
| SPRC_OK              | The parameters have been read successfully                         |

### Remarks

## SpRcClient::GetIsdbtPars

Get ISDB-T modulation parameters.

```
virtual SPRC_RESULT SpRcClient::GetIsdbtPars(  
    [out] SpRcIsdbtPars& IsdbtPars // ISDB-T parameters  
);
```

### Parameters

*IsdbtPars*

ISDB-T modulation parameters, see **Struct SpRcIsdbtPars**.

### Result

| SPRC_RESULT          | Meaning   |
|----------------------|---|
| SPRC_E_COMMUNICATION | An error has occurred in the communication with the playout server        |
| SPRC_E_NO_PORT       | Invalid operation because no port is selected                             |
| SPRC_E_NOT_ISDBT     | Invalid operation because the port is operating in ISDB-T modulation mode |
| SPRC_E_NOT_MOD       | Invalid operation because the port is not a modulation port               |
| SPRC_OK              | The modulation parameters have been read successfully                     |

### Remarks

## SpRcClient::GetIqGain

Get IQ gain parameter.

```
virtual SPRC_RESULT SpRcClient::GetIqGain(  
    [out] int& IqGain           // IQ gain  
);
```

### Parameters

*IqGain*

The gain of the IQ signal.

### Result

| SPRC_RESULT          | Meaning  |
|----------------------|--|
| SPRC_E_COMMUNICATION | An error has occurred in the communication with the playout server |
| SPRC_E_NO_PORT       | Invalid operation because no port is selected                      |
| SPRC_E_NOT_MOD       | Invalid operation because the port is not a modulation port        |
| SPRC_OK              | The modulation parameters have been read successfully              |

### Remarks

## SpRcClient::GetModPars

Get modulation parameters.

```
virtual SPRC_RESULT SpRcClient::GetModPars (  
    [out] SpRcModPars& ModPars // Modulation parameters  
);
```

### Parameters

*ModPars*

Modulation parameters, see **Struct SpRcModPars**.

### Result

| SPRC_RESULT          | Meaning  |
|----------------------|--|
| SPRC_E_COMMUNICATION | An error has occurred in the communication with the playout server |
| SPRC_E_NO_PORT       | Invalid operation because no port is selected                      |
| SPRC_E_NOT_MOD       | Invalid operation because the port is not a modulation port        |
| SPRC_OK              | The modulation parameters have been read successfully              |

### Remarks

## SpRcClient::GetPayoutInfo

Get static payout information.

```
virtual SPRC_RESULT SpRcClient::GetPayoutInfo(  
    [out] SpRcPayoutInfo& PoInfo    // Static payout info  
);
```

### Parameters

*PoInfo*

Payout information, see Struct `SpRcPayoutInfo`.

### Result

| SPRC_RESULT          | Meaning   |
|----------------------|---|
| SPRC_E_COMMUNICATION | An error has occurred in the communication with the payout server |
| SPRC_E_NO_PORT       | Invalid operation because no port is selected                     |
| SPRC_OK              | The payout information has been read successfully                 |

### Remarks

## SpRcClient::GetPayoutStatus

Get dynamic payout status.

```
virtual SPRC_RESULT SpRcClient::GetPayoutStatus(  
    [out] SpRcPayoutStatus& PoStatus    // Dynamic payout status  
);
```

### Parameters

*PoInfo*

Payout information, see Struct **SpRcPayoutInfo**.

### Result

| SPRC_RESULT          | Meaning   |
|----------------------|---|
| SPRC_E_COMMUNICATION | An error has occurred in the communication with the payout server |
| SPRC_E_NO_PORT       | Invalid operation because no port is selected                     |
| SPRC_OK              | The payout status has been read successfully                      |

### Remarks

## SpRcClient::GetRfPars

Get RF parameters.

```
virtual SPRC_RESULT SpRcClient::GetRfPars(  
    [out] SpRcRfPars& RfPars           // RF parameters  
);
```

### Parameters

*RfPars*

RF parameters, see Struct `SpRcRfPars`.

### Result

| SPRC_RESULT          | Meaning  |
|----------------------|--|
| SPRC_E_COMMUNICATION | An error has occurred in the communication with the playout server |
| SPRC_E_NO_PORT       | Invalid operation because no port is selected                      |
| SPRC_E_NOT_MOD       | Invalid operation because the port is not a modulation port        |
| SPRC_OK              | The RF parameters have been read successfully                      |

### Remarks

## SpRcClient::GetSignalSource

Get current signal source (from file / test-generator).

```
virtual SPRC_RESULT SpRcClient::GetSignalSource(
    [out] int& SignalSource // Signal source
);
```

### Parameters

*SignalSource*

Current signal source.

| Value               | Meaning  |
|---------------------|--|
| SPRC_FROM_FILE      | Data is read from file   |
| SPRC_TEST_GENERATOR | The test-signal generator is used to generate an output signal |

### Result

| SPRC_RESULT          | Meaning  |
|----------------------|--|
| SPRC_E_COMMUNICATION | An error has occurred in the communication with the playout server |
| SPRC_E_NO_PORT       | Invalid operation because no port is selected                      |
| SPRC_OK              | The signal source has been read successfully                       |

### Remarks

## SpRcClient::GetSpiPars

Get DVB-SPI transmission parameters.

```
virtual SPRC_RESULT SpRcClient::GetSpiPars (  
    [out] SpRcAsiPars& SpiPars // DVB-SPI parameters  
);
```

### Parameters

*SpiPars*

DVB-SPI transmission parameters, see **Struct SpRcSpiPars**.

### Result

| SPRC_RESULT          | Meaning  |
|----------------------|--|
| SPRC_E_COMMUNICATION | An error has occurred in the communication with the playout server |
| SPRC_E_NO_PORT       | Invalid operation because no port is selected                      |
| SPRC_E_NOT_SPI       | Invalid operation because the port is not a DVB-SPI port           |
| SPRC_OK              | The DVB-SPI transmission parameters have been read successfully    |

### Remarks

## SpRcClient::GetTsgPars

Get test-signal generator parameters.

```
virtual SPRC_RESULT SpRcClient::GetTsgPars (  
    [out] SpRcTsgPars& TsgPars // Test-signal generator parameters  
);
```

### Parameters

*TsgPars*

Test-signal generator parameters, see **Struct SpRcTsgPars**.

### Result

| SPRC_RESULT             | Meaning   |
|-------------------------|---|
| SPRC_E_COMMUNICATION    | An error has occurred in the communication with the playout server                            |
| SPRC_E_NO_PORT          | Invalid operation because no port is selected   |
| SPRC_E_OP_NOT_SUPPORTED | Invalid operation because StreamXpress is not currently running in test-signal generator mode |
| SPRC_OK                 | The parameters have been read successfully  |

### Remarks

## SpRcClient::GetTsoipPars

Get TSolP transmission parameters.

```
virtual SPRC_RESULT SpRcClient::GetTsoipPars(  
    [out] SpRcTsoipPars& TsoipPars // TSoIP parameters  
);
```

### Parameters

*TsoipPars*

TSolP transmission parameters, see Struct **SpRcTsoipPars**.

### Result

| SPRC_RESULT          | Meaning  |
|----------------------|--|
| SPRC_E_COMMUNICATION | An error has occurred in the communication with the playout server |
| SPRC_E_NO_PORT       | Invalid operation because no port is selected                      |
| SPRC_E_NOT_TSOIP     | Invalid operation because the port is not a TSolP port             |
| SPRC_OK              | The TSolP transmission parameters have been read successfully      |

### Remarks

## SpRcClient::GetUseNit

Checking whether NIT is used for deriving parameters.

```
virtual SPRC_RESULT SpRcClient::GetUseNit(  
    [out] bool& UseNit  
);
```

### Parameters

*UseNit*

True if and only if StreamXpress will try to use NIT to set the modulation parameters.

### Result

| SPRC_RESULT          | Meaning  |
|----------------------|--|
| SPRC_E_COMMUNICATION | An error has occurred in the communication with the playout server |
| SPRC_E_NO_PORT       | Invalid operation because no port is selected                      |
| SPRC_OK              | The UseNit parameter has been read successfully                    |

### Remarks

## SpRcClient::Normalise

Normalise the multipath channel modelling.

```
virtual SPRC_RESULT SpRcClient::Normalise();
```

### Parameters

### Result

| SPRC_RESULT          | Meaning  |
|----------------------|--|
| SPRC_E_NO_PORT       | Invalid operation because no port is selected                      |
| SPRC_E_NOT_MOD       | Invalid operation because the port is not a modulation port        |
| SPRC_E_COMMUNICATION | An error has occurred in the communication with the playout server |
| SPRC_OK              | The channel modelling settings have been normalised                |

### Remarks

## SpRcClient::OpenChannelModellingFile

Open file with settings for channel modelling.

```
virtual SPRC_RESULT SpRcClient::OpenChannelModellingFile (
    [in] std::wstring& Filename // Filename
);
```

### Parameters

*Filename*

Filename to be opened.

### Result

| SPRC_RESULT              | Meaning  |
|--------------------------|--|
| SPRC_E_FILE_CANT_FIND    | Can't find a file with the specified filename                      |
| SPRC_E_FILE_SYNTAX_ERROR | The specified file contains a syntax error                         |
| SPRC_E_COMMUNICATION     | An error has occurred in the communication with the playout server |
| SPRC_E_NO_PORT           | Invalid operation because no port is selected                      |
| SPRC_E_NOT_MOD           | Invalid operation because the port is not a modulation port        |
| SPRC_OK                  | The channel modelling settings file has been loaded successfully   |

### Remarks

## SpRcClient::OpenFile

Open file for playout.

```
virtual SPRC_RESULT SpRcClient::OpenFile(  
    [in] std::wstring& Filename // Filename  
);
```

### Parameters

*Filename*

Filename to be opened.

### Result

| SPRC_RESULT           | Meaning  |
|-----------------------|--|
| SPRC_E_FILE_CANT_FIND | Can't find a file with the specified filename                      |
| SPRC_E_COMMUNICATION  | An error has occurred in the communication with the playout server |
| SPRC_OK               | The playout file has been opened successfully                      |

### Remarks

## SpRcClient::SaveChannelModellingSettings

Save the channel modelling settings to a file.

```
virtual SPRC_RESULT SpRcClient::SaveChannelModellingSettings (  
    [in] std::wstring& Filename // Filename  
);
```

### Parameters

*Filename*

Filename to be opened.

### Result

| SPRC_RESULT             | Meaning  |
|-------------------------|--|
| SPRC_E_FILE_CANT_CREATE | Error opening the file for writing                                 |
| SPRC_E_COMMUNICATION    | An error has occurred in the communication with the playout server |
| SPRC_E_NO_PORT          | Invalid operation because no port is selected                      |
| SPRC_E_NOT_MOD          | Invalid operation because the port is not a modulation port        |
| SPRC_OK                 | The channel modelling settings have been saved successfully        |

### Remarks

## SpRcClient::SaveSettings

Save the settings to a file.

```
virtual SPRC_RESULT SpRcClient::SaveSettings(  
    [in] std::wstring& Filename // Filename  
);
```

### Parameters

*Filename*

Filename to be opened.

### Result

| SPRC_RESULT             | Meaning  |
|-------------------------|--|
| SPRC_E_FILE_CANT_CREATE | Error opening the file for writing                                 |
| SPRC_E_COMMUNICATION    | An error has occurred in the communication with the playout server |
| SPRC_OK                 | The settings have been saved successfully                          |

### Remarks

## SpRcClient::SetAsiPars

Set DVB-ASI transmission parameters.

```
virtual SPRC_RESULT SpRcClient::SetAsiPars (
    [in] SpRcAsiPars AsiPars // ASI parameters
);
```

### Parameters

*AsiPars*

DVB-ASI transmission parameters, see **Struct SpRcAsiPars**.

### Result

| SPRC_RESULT          | Meaning  |
|----------------------|--|
| SPRC_E_COMMUNICATION | An error has occurred in the communication with the playout server                             |
| SPRC_E_NO_PORT       | Invalid operation because no port is selected  |
| SPRC_E_NOT_ASI       | Invalid operation because the port is not an ASI port or is operating in SDI mode              |
| SPRC_E_POLARITY      | The polarity specified in <i>AsiPars</i> is not supported by the device                        |
| SPRC_E_TXMODE        | The transmit mode specified in <i>AsiPars</i> is not compatible with the Transport-Stream file |
| SPRC_OK              | The DVB-ASI transmission parameters have been set successfully                                 |

### Remarks

## SpRcClient::SetChannelModellingPars

Set Channel Modelling parameters.

```
virtual SPRC_RESULT SpRcClient::SetChannelModellingPars (  
    [in] SpRcCmPars CmPars           // Channel Modelling parameters  
);
```

### Parameters

*CmPars*

Channel Modelling parameters, see **Struct SpRcCmPars**.

### Result

| SPRC_RESULT          | Meaning  |
|----------------------|--|
| SPRC_E_COMMUNICATION | An error has occurred in the communication with the playout server |
| SPRC_E_NO_PORT       | Invalid operation because no port is selected                      |
| SPRC_E_NOT_MOD       | Invalid operation because the port is not a modulation port        |
| SPRC_OK              | The Channel Modelling parameters have been set successfully        |

### Remarks

## SpRcClient::SetCmmbPars

Set CMMB parameters.

```
virtual SPRC_RESULT SpRcClient::SetCmmbPars (  
    [in] SpRcCmmbPars CmmbPars           // CMMB parameters  
);
```

### Parameters

*CmmbPars*

CMMB parameters, see **Struct SpRcCmmbPars**.

### Result

| SPRC_RESULT          | Meaning  |
|----------------------|--|
| SPRC_E_COMMUNICATION | An error has occurred in the communication with the playout server |
| SPRC_E_NO_PORT       | Invalid operation because no port is selected                      |
| SPRC_E_NOT_MOD       | Invalid operation because the port is not a modulation port        |
| SPRC_E_NOT_CMMB      | Invalid operation because CMMB modulation is not configured        |
| SPRC_OK              | The parameters have been set successfully                          |

### Remarks

## SpRcClient::SetDvbT2Group

Set DVB-T2 standard parameter set; e.g. 'V125' parameters.

```
virtual SPRC_RESULT SpRcClient::SetDvbT2Group(  
    [in] SpRcDvbT2Group DvbT2Group // DVB-T2 parameter set  
);
```

### Parameters

*DvbT2Group*

DVB-T2 standard parameter set, see Struct `SpRcDvbT2Group`.

### Result

| SPRC_RESULT          | Meaning  |
|----------------------|--|
| SPRC_E_COMMUNICATION | An error has occurred in the communication with the playout server |
| SPRC_E_NO_PORT       | Invalid operation because no port is selected                      |
| SPRC_E_NOT_MOD       | Invalid operation because the port is not a modulation port        |
| SPRC_E_NOT_DVB-T2    | Invalid operation because DVB-T2 modulation is not configured      |
| SPRC_OK              | The parameters have been set successfully                          |

### Remarks

## SpRcClient::SetDvbT2Pars

Set DVB-T2 parameters.

```
virtual SPRC_RESULT SpRcClient::SetDvbT2Pars (
    [in] SpRcDvbT2Pars DvbT2Pars // DVB-T2 parameters
);
```

### Parameters

*DvbT2Pars*

DVB-T2 parameters, see **Struct SpRcDvbT2Pars**.

### Result

| SPRC_RESULT          | Meaning  |
|----------------------|--|
| SPRC_E_COMMUNICATION | An error has occurred in the communication with the playout server |
| SPRC_E_NO_PORT       | Invalid operation because no port is selected                      |
| SPRC_E_NOT_MOD       | Invalid operation because the port is not a modulation port        |
| SPRC_E_NOT_DVB-T2    | Invalid operation because DVB-T2 modulation is not configured      |
| SPRC_OK              | The parameters have been set successfully                          |

### Remarks

## SpRcClient::SetHwNoisePars

Set Noise parameters for modulators DTA-107 and DTA-2107.

```
virtual SPRC_RESULT SpRcClient::SetHwNoisePars (  
    [in] SpRcHwNoisePars HwNoisePars // Noise parameters  
);
```

### Parameters

*HwNoisePars*

Noise parameters, see Struct `SpRcHwNoisePars`.

### Result

| SPRC_RESULT          | Meaning  |
|----------------------|--|
| SPRC_E_COMMUNICATION | An error has occurred in the communication with the playout server |
| SPRC_E_NO_PORT       | Invalid operation because no port is selected                      |
| SPRC_E_NOT_MOD       | Invalid operation because the port is not a modulation port        |
| SPRC_OK              | The parameters have been set successfully                          |

### Remarks

## SpRcClient::SetIsdbtPars

Set ISDB-T modulation parameters.

```
virtual SPRC_RESULT SpRcClient::SetIsdbtPars (  
    [in] SpRcIsdbtPars  IsdbtPars    // ISDB-T parameters  
);
```

### Parameters

*IsdbtPars*

ISDB-T modulation parameters, see **Struct SpRcIsdbtPars**.

### Result

| SPRC_RESULT          | Meaning   |
|----------------------|---|
| SPRC_E_COMMUNICATION | An error has occurred in the communication with the playout server        |
| SPRC_E_NO_PORT       | Invalid operation because no port is selected                             |
| SPRC_E_NOT_ISDBT     | Invalid operation because the port is operating in ISDB-T modulation mode |
| SPRC_E_NOT_MOD       | Invalid operation because the port is not a modulation port               |
| SPRC_OK              | The modulation parameters have been set successfully                      |

### Remarks

## SpRcClient::SetIqGain

Set IQ gain parameter.

```
virtual SPRC_RESULT SpRcClient::SetIqGain(  
    [in] int IqGain // IQ gain  
);
```

### Parameters

*IqGain*

The gain of the IQ signal.

### Result

| SPRC_RESULT          | Meaning  |
|----------------------|--|
| SPRC_E_COMMUNICATION | An error has occurred in the communication with the playout server |
| SPRC_E_NO_PORT       | Invalid operation because no port is selected                      |
| SPRC_E_NOT_MOD       | Invalid operation because the port is not a modulation port        |
| SPRC_OK              | The modulation parameters have been set successfully               |

### Remarks

## SpRcClient::SetLoopFlags

Set loop-adaptation flags.

```
virtual SPRC_RESULT SpRcClient::SetLoopFlags(
    [in] int LoopFlags // Loop-adaptation flags
);
```

### Parameters

*LoopFlags*

Loop-adaptation flags encoded in flags that may be OR-ed together.

| Value          | Meaning                   |
|----------------|---------------------------|
| SPRC_LOOP_CC   | Adapt continuity counters |
| SPRC_LOOP_PCR  | Adapt PCR                 |
| SPRC_LOOP_TDT  | Adapt TDT                 |
| SPRC_LOOP_WRAP | Auto wrap-around          |

### Result

| SPRC_RESULT          | Meaning  |
|----------------------|--|
| SPRC_E_COMMUNICATION | An error has occurred in the communication with the playout server |
| SPRC_E_NO_PORT       | Invalid operation because no port is selected                      |
| SPRC_OK              | The loop-adaptation flags have been set successfully               |

### Remarks

## SpRcClient::SetModPars

Set modulation parameters for all modulation standards except ISDB-T and DVB-T2.

```
virtual SPRC_RESULT SpRcClient::SetModPars (  
    [in] SpRcModPars ModPars          // Modulation parameters  
);
```

### Parameters

*ModPars*

Modulation parameters, see **Struct SpRcModPars**.

### Result

| SPRC_RESULT          | Meaning  |
|----------------------|--|
| SPRC_E_COMMUNICATION | An error has occurred in the communication with the playout server |
| SPRC_E_NO_PORT       | Invalid operation because no port is selected                      |
| SPRC_E_NOT_MOD       | Invalid operation because the port is not a modulation port        |
| SPRC_OK              | The modulation parameters have been set successfully               |

### Remarks

## SpRcClient::SetPlayoutState

Set playout state (play/pause/stop).

```
virtual SPRC_RESULT SpRcClient::SetPlayoutState(
    [in] int PlayoutState // Playout state
);
```

### Parameters

*PlayoutState*

New playout state.

| Value            | Meaning |
|------------------|---------|
| SPRC_STATE_PAUSE | Pause   |
| SPRC_STATE_PLAY  | Play    |
| SPRC_STATE_STOP  | Stop    |

### Result

| SPRC_RESULT          | Meaning  |
|----------------------|--|
| SPRC_E_COMMUNICATION | An error has occurred in the communication with the playout server |
| SPRC_E_INV_STATE     | Invalid playout state  |
| SPRC_E_NO_PORT       | Invalid operation because no port is selected                      |
| SPRC_OK              | The playout state has been set successfully                        |

### Remarks

## SpRcClient::SetRfPars

Set RF parameters.

```
virtual SPROC_RESULT SpRcClient::SetRfPars(
    [in] SpRcRfPars  RfPars           // RF parameters
);
```

### Parameters

*RfPars*

RF parameters, see Struct `SpRcPars`.

### Result

| SPRC_RESULT          | Meaning   |
|----------------------|---|
| SPRC_E_COMMUNICATION | An error has occurred in the communication with the playout server                          |
| SPRC_E_INV_FREQ      | The centre frequency in <i>RfPars</i> is not supported by the upconverter on this modulator |
| SPRC_E_INV_LEVEL     | The level in <i>RfPars</i> is not supported by this modulator                               |
| SPRC_E_NO_PORT       | Invalid operation because no port is selected   |
| SPRC_E_NOT_MOD       | Invalid operation because the port is not a modulation port                                 |
| SPRC_OK              | The RF parameters have been set successfully  |

### Remarks

## SpRcClient::SetSignalSource

Change signal source (from file / test-generator).

```
virtual SPRC_RESULT SpRcClient::SetSignalSource(
    [in] int SignalSource // Signal source
);
```

### Parameters

*SignalSource*

New signal source.

| Value               | Meaning  |
|---------------------|--|
| SPRC_FROM_FILE      | Data is read from file   |
| SPRC_TEST_GENERATOR | The test-signal generator is used to generate an output signal |

### Result

| SPRC_RESULT             | Meaning  |
|-------------------------|--|
| SPRC_E_COMMUNICATION    | An error has occurred in the communication with the playout server |
| SPRC_E_OP_NOT_SUPPORTED | Current modulation type is not supported                           |
| SPRC_E_NO_PORT          | Invalid operation because no port is selected                      |
| SPRC_OK                 | The signal source has been changed successfully                    |

### Remarks

## SpRcClient::SetSpiPars

Set DVB-SPI transmission parameters.

```
virtual SPRC_RESULT SpRcClient::SetSpiPars(
    [in] SpRcSpiPars SpiPars // DVB-SPI parameters
);
```

### Parameters

*SpiPars*

DVB-SPI transmission parameters, see **Struct SpRcSpiPars**.

### Result

| SPRC_RESULT          | Meaning  |
|----------------------|--|
| SPRC_E_COMMUNICATION | An error has occurred in the communication with the playout server                             |
| SPRC_E_NO_PORT       | Invalid operation because no port is selected  |
| SPRC_E_NOT_SPI       | Invalid operation because the port is not a DVB-SPI port                                       |
| SPRC_E_TXMODE        | The transmit mode specified in <i>SpiPars</i> is not compatible with the Transport-Stream file |
| SPRC_OK              | The DVB-SPI transmission parameters have been set successfully                                 |

### Remarks

## SpRcClient::SetTsgPars

Set test-signal generation parameters.

```
virtual SPRC_RESULT SpRcClient::SetTsoipPars(  
    [in] SpRcTsgPars TsgPars // test-signal generation parameters  
);
```

### Parameters

*TsgPars*

Test-signal generation parameters, see Struct `SpRcTsgPars`.

### Result

| SPRC_RESULT             | Meaning   |
|-------------------------|---|
| SPRC_E_COMMUNICATION    | An error has occurred in the communication with the playout server                            |
| SPRC_E_NO_PORT          | Invalid operation because no port is selected   |
| SPRC_E_OP_NOT_SUPPORTED | Invalid operation because StreamXpress is not currently running in test-signal generator mode |
| SPRC_OK                 | The parameters have been set successfully   |

### Remarks

## SpRcClient::SetTsoipPars

Set TSolP transmission parameters.

```
virtual SPRC_RESULT SpRcClient::SetTsoipPars (  
    [in] SpRcTsoipPars TsoipPars    // TSoIP parameters  
);
```

### Parameters

*TsoipPars*

TSolP transmission parameters, see Struct **SpRcTsoipPars**.

### Result

| SPRC_RESULT          | Meaning  |
|----------------------|--|
| SPRC_E_COMMUNICATION | An error has occurred in the communication with the playout server |
| SPRC_E_NO_PORT       | Invalid operation because no port is selected                      |
| SPRC_E_NOT_TSOIP     | Invalid operation because the port is not a TSolP port             |
| SPRC_OK              | The TSolP transmission parameters have been set successfully       |

### Remarks

## SpRcClient::SetTsRate

Set Transport-Stream rate

```
virtual SPRC_RESULT SpRcClient::SetTsRate(  
    [in] Int    TsRate           // Transport-Stream rate  
);
```

### Parameters

*TsRate*

Transport-Stream rate in bits per second; 188 bytes per Transport Packets

### Result

| SPRC_RESULT          | Meaning  |
|----------------------|--|
| SPRC_E_COMMUNICATION | An error has occurred in the communication with the playout server |
| SPRC_E_NO_PORT       | Invalid operation because no port is selected                      |
| SPRC_OK              | The rate has been set successfully                                 |

### Remarks

## SpRcClient::SetUseNit

Enable or disable the use of NIT for deriving modulation parameters

```
virtual SPRC_RESULT SpRcClient::SetUseNit(  
    [in] Bool UseNit  
);
```

### Parameters

*UseNit*

Whether or not NIT should be used.

### Result

| SPRC_RESULT          | Meaning  |
|----------------------|--|
| SPRC_E_COMMUNICATION | An error has occurred in the communication with the playout server |
| SPRC_E_NO_PORT       | Invalid operation because no port is selected                      |
| SPRC_OK              | The parameter has been set successfully                            |

### Remarks

## SpRcClient::WaitForCondition

Wait for a certain condition.

```
virtual SPRC_RESULT SpRcClient::WaitForCondition(
    [in] int Condition,          // Playout state to wait for
    [in] int TimeOut           // Maximum time to wait in ms
);
```

### Parameters

*Condition*

Condition to wait for.

| Value             | Meaning  |
|-------------------|--|
| SPRC_COND_STOPPED | Playout server is in a stopped state; In this context, pause is not considered a stopped state |

*TimeOut*

Time-out period in ms. If this parameter is -1 no time out is applied.

### Result

| SPRC_RESULT          | Meaning  |
|----------------------|--|
| SPRC_E_COMMUNICATION | An error has occurred in the communication with the playout server |
| SPRC_E_INV_CONDITION | An invalid condition has been specified                            |
| SPRC_OK              | The condition has occurred   |
| SPRC_TIME_OUT        | The time out has triggered   |

### Remarks